

## LIST OF FIGURES

<i>Fig 2.1 Timeline for the development of IEEE 802.11ac Wave-2 .....</i>	<i>13</i>
<i>Fig 2.2 Data Transfer Mechanism with Beamforming.....</i>	<i>16</i>
<i>Fig 2.3a Channel Sounding - NDPA and NDP.....</i>	<i>16</i>
<i>Fig 2.3b Channel Sounding - Feedback and Steering Matrices.....</i>	<i>17</i>
<i>Fig 2.4 Range Improvement due to Transmit Beam Forming.....</i>	<i>18</i>
<i>Fig 3.1 VPQ System Model.....</i>	<i>33</i>
<i>Fig 3.2 Functional Example - Adapting the Aggregated Frame.....</i>	<i>41</i>
<i>Fig 3.3 Resource Allocation using DL-ARBI.....</i>	<i>43</i>
<i>Fig 3.4 A Heuristic Resource Allocation Algorithm .....</i>	<i>44</i>
<i>Fig 3.5 ADWISER.....</i>	<i>46</i>
<i>Fig 3.6 Data Flow in ADWISER.....</i>	<i>47</i>
<i>Fig 3.7 Proposed QoE-Aware Scheduling Framework.....</i>	<i>50</i>
<i>Fig 4.1 Throughput vs. MCS; SGI and 20 MHz Bandwidth.....</i>	<i>76</i>
<i>Fig 4.2 Throughput vs. MCS; Long GI and 20 MHz Bandwidth.....</i>	<i>77</i>
<i>Fig 4.3 Throughput vs. MCS; SGI and 40 MHz Bandwidth.....</i>	<i>77</i>
<i>Fig 4.4 Throughput vs. MCS; Long GI and 40 MHz Bandwidth.....</i>	<i>78</i>
<i>Fig 4.5 Mean Delay vs. MCS, SGI, 20 MHz Bandwidth.....</i>	<i>78</i>
<i>Fig 4.6 Mean Delay vs. MCS, long GI, 20 MHz Bandwidth.....</i>	<i>79</i>
<i>Fig 4.7 Mean Delay vs. MCS, SGI, 40 MHz Bandwidth.....</i>	<i>79</i>
<i>Fig 4.8 Mean Delay vs. MCS, long GI, 40 MHz Bandwidth.....</i>	<i>80</i>
<i>Fig 4.9 Mean Jitter vs. MCS, short GI, 20 MHz Bandwidth.....</i>	<i>81</i>
<i>Fig 4.10 Mean Jitter vs. MCS, long GI, 20 MHz Bandwidth.....</i>	<i>81</i>
<i>Fig 4.11 Mean Jitter vs. MCS for short GI with 40 MHz Bandwidth.....</i>	<i>82</i>
<i>Fig 4.12 Mean Jitter vs. MCS for long GI with 40 MHz Bandwidth.....</i>	<i>82</i>
<i>Fig 4.13 Throughput vs. MCS for SGI with 20, 40, 80, 160 MHz Bandwidth.....</i>	<i>83</i>
<i>Fig 4.14 Throughput vs. MCS for long GI with 20, 40, 80, 160 MHz Bandwidth ....</i>	<i>83</i>
<i>Fig 4.15 Mean delay vs. MCS for SGI with 20, 40, 80, 160 MHz Bandwidth.....</i>	<i>84</i>
<i>Fig 4.16 Mean delay vs. MCS for LGI with 20, 40, 80, 160 MHz Bandwidth.....</i>	<i>84</i>
<i>Fig 4.17 Mean jitter vs. MCS for SGI with 20, 40, 80, 160 MHz Bandwidth.....</i>	<i>85</i>
<i>Fig 4.18 Mean jitter vs. MCS for long GI with 20, 40, 80, 160 MHz Bandwidth.....</i>	<i>85</i>
<i>Fig 4.19a 802.11n &amp; 11ac response to Ideal WiFi for 1,2,3,4 SS, 20 MHz CBW.....</i>	<i>91</i>

*Fig 4.19b 802.11n & 11ac response to Ideal WiFi for 1,2,3,4 SS, 40 MHz CBW..... 92*

*Fig 4.19c 802.11ac response to Ideal WiFi for 1,2,3,4 SS, 80 MHz CBW ..... 92*

*Fig 4.19d 802.11ac response to Ideal Wi-Fi for 1,2,3,4 SS, 160 MHz CBW..... 93*

*Fig 4.20a: 802.11ac & 802.11n Response to 'Minstrel' for 1,2,3,4 SS, 20 MHz CBW ..... 94*

*Fig 4.20b: 802.11ac & 802.11n Response to 'Minstrel' for 1,2,3,4 SS; 40 MHz CBW ..... 95*

*Fig 4.20c: 802.11ac Protocol Response to Minstrel; CBW=80 MHz..... 96*

*Fig 4.20d: 802.11ac Protocol Response to Minstrel; CBW=160 MHz..... 96*

*Fig 4.21: 802.11ac Response to 'Ideal' RA for 1,2,3,4 SS; 80 MHz CBW under the influence of GI..... 97*

*Fig 4.22a 802.11ac Response to Minstrel for 1,2,3,4 SS; CBW 20 MHz under the influence of GI..... 98*

*Fig 4.22b 802.11ac Response to Minstrel for 1,2,3,4 SS; CBW 40 MHz under the influence of GI..... 98*

*Fig 4.22c 802.11ac Response to Minstrel for 1,2,3,4 SS; CBW 80 MHz under the influence of GI..... 99*

*Fig 4.22d 802.11ac Response to Minstrel for 1,2,3,4 SS; CBW 160 MHz under the influence of GI..... 99*

*Fig 4.23a: 802.11n Response to Minstrel for 1,2,3,4 SS; CBW 20 MHz under the influence of GI..... 100*

*Fig 4.23b: 802.11n Response to Minstrel for 1,2,3,4 SS; CBW 40 MHz under the influence of GI..... 100*

*Fig 4.24a: 802.11ac Response to Ideal & Minstrel for 1,2,3,4 SS; CBW 20 MHz.. 101*

*Fig 4.24b: 802.11ac Response to Ideal & Minstrel for 1,2,3,4 SS; CBW 40 MHz.. 102*

*Fig 4.24c: 802.11ac Response to Ideal & Minstrel for 1,2,3,4 SS; CBW 80 MHz.. 102*

*Fig 4.24d: 802.11ac Response to Ideal & Minstrel for 1,2,3,4 SS; CBW 160 MHz 103*

*Fig 4.25a: Observed & selected rates-802.11ac-'Ideal'-1,2,3,4 SS; CBW 20MHz.. 104*

*Fig 4.25b: Observed & selected rates-802.11ac-'Ideal'-1,2,3,4 SS; CBW 40MHz.. 104*

*Fig 4.25c: Observed & selected rates-802.11ac-'Ideal'-1,2,3,4 SS; CBW 80 MHz. 105*

*Fig 4.25d: Observed & selected rates-802.11ac-'Ideal'-1,2,3,4 SS; CBW 160 MHz ..... 105*

*Fig 4.26a: Observed & selected rates-802.11ac-Minstrel-1,2,3,4 SS;CBW 20MHz 106*

*Fig 4.26b: Observed & selected rates-802.11ac-Minstrel-1,2,3,4 SS;CBW 40MHz 106*

*Fig 4.26c: Observed & selected rates-802.11ac-Minstrel-1,2,3,4 SS;CBW 80MHz 107*

<i>Fig 4.26d: Observed &amp; selected rates-802.11ac-Minstrel-1,2,3,4 SS;CBW 160MHz</i>	107
<i>Fig 4.27: Observed &amp; selected rates as standard deviation for 802.11ac Ideal and Minstrel RA</i>	109
<i>Fig 4.28 Transmission with Spatial Expansion</i>	112
<i>Fig 4.29 Transmission with Beam Forming</i>	113
<i>Fig 4.30a Constellation Diagram - CBW=160 MHz, MCS=9, 4×1 MIMO</i>	114
<i>Fig 4.30b Constellation Diagram - CBW=160 MHz, MCS=9, 2×1 MIMO</i>	114
<i>Fig 4.30c Constellation Diagram - CBW=40 MHz, MCS=9, 4×1 MIMO</i>	115
<i>Fig 4.30d Constellation Diagram - CBW=40 MHz, MCS=9, 3×1 MIMO</i>	115
<i>Fig 4.30e Constellation Diagram - CBW=40 MHz, MCS=9, 2×1 MIMO</i>	116
<i>Fig 4.31a Constellation Diagram - CBW=160 MHz, MCS=1, 4×1 MIMO</i>	116
<i>Fig 4.31b Constellation Diagram - CBW=160 MHz, MCS=1, 3×1 MIMO</i>	117
<i>Fig 4.31c Constellation Diagram - CBW=160 MHz, MCS=1, 2×1 MIMO</i>	117
<i>Fig 4.31d Constellation Diagram - CBW=40 MHz, MCS=1, 4×1 MIMO</i>	118
<i>Fig 4.31e Constellation Diagram - CBW=40 MHz, MCS=1, 3×1 MIMO</i>	118
<i>Fig 4.31f Constellation Diagram - CBW=40 MHz, MCS=1, 2×1 MIMO</i>	119
<i>Fig 4.32a EVM (max) for CBW=40 &amp; 160 MHz, MCS=1 to 9, 2×1 MIMO</i>	120
<i>Fig 4.32b EVM (max) for CBW=40 &amp; 160 MHz, MCS=1 to 9, 3×1 MIMO</i>	120
<i>Fig 4.32c EVM (max) for CBW=40 &amp; 160 MHz, MCS=1 to 9, 4×1 MIMO</i>	120
<i>Fig 4.33a EVM (rms) for CBW=40 MHz, MCS=1 to 9, 2×1, 3×1 &amp; 4×1 MIMO configuration with Spatial Expansion and TBF</i>	121
<i>Fig 4.33b EVM (rms) for CBW=160 MHz, MCS=1 to 9, 2×1, 3×1 &amp; 4×1 MIMO configuration with Spatial Expansion and TBF</i>	122
<i>Fig 4.34a Mean received channel power (Watts) per STS with TBF for CBW 40 MHz</i>	123
<i>Fig 4.34b Mean received channel power in Watts per STS with TBF for CBW 160 MHz</i>	123
<i>Fig 4.35a Mean received channel power in Watts with TBF for CBW 20 MHz...</i>	124
<i>Fig 4.35b Mean received channel power in Watts with TBF for CBW 40 MHz...</i>	124
<i>Fig 4.35c Mean received channel power in Watts with TBF for CBW 80 MHz...</i>	125
<i>Fig 4.35d Mean received channel power in Watts with TBF for CBW 160 MHz.</i>	125
<i>Fig 4.36 MU-MIMO Scenario-1</i>	130
<i>Fig 4.37 MU-MIMO Scenario-2</i>	132

<i>Fig 4.38 MU-MIMO Scenario-3</i> .....	133
<i>Fig 5.1 Block Diagram of the Proposed Scheduler</i> .....	144
<i>Fig 5.2 TXBF/MU-MIMO Subcomponent</i> .....	147
<i>Fig 5.3 Scheduler Control in a Multi-user Scenario</i> .....	155
<i>FigA4.1 Network Entry</i> .....	172
<i>FigA4.2 Uplink Data Flow (MS-BS) Process</i> .....	174
<i>Fig A4.3 Downlink Data Flow (BS-MS) Process</i> .....	175
<i>Fig A4.4 2D view of the OFDMA Frame</i> .....	176
<i>Fig A7.1: Example OF EDCA TXOP Sharing</i> .....	185
<i>Fig A7.2: Downlink MU-MIMO Transmission</i> .....	186
<i>Fig A7.3 VHT Preamble</i> .....	187
<i>Fig A7.4: Frame Format of A-MPDU &amp; Compressed Block ACK</i> .....	188
<i>Fig A7.5: Structure of VHT DL MU-MIMO</i> .....	188
<i>Fig A7.6: 802.11ac WLAN System architecture for 2-user case</i> .....	189
<i>Fig A7.7: VHT Packet format for 802.11ac WLAN Systems</i> .....	190
<i>Fig-A7.8: Channel sounding in MU-MIMO Transmission</i> .....	191
<i>Fig A7.9: MU-MIMO Transmission</i> .....	192