


Name:													
Enrolment No:													
UPES End Semester Examination, December 2023													
Course: Numerical Methods in Scientific Computing Program: BSc (H) Physics Course Code: PHYS 3026		Semester: V Time : 03 hrs. Max. Marks: 100											
Instructions:													
SECTION A (5Qx4M=20Marks)													
S. No.		Marks	CO										
Q1	Using the data given below, prepare a table up to third divided differences. <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">x</td> <td style="padding: 2px 10px;">$f(x)$</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">-0.1</td> <td style="padding: 2px 10px;">5.30000</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">0.0</td> <td style="padding: 2px 10px;">2.00000</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">0.2</td> <td style="padding: 2px 10px;">3.19000</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">0.3</td> <td style="padding: 2px 10px;">1.00000</td> </tr> </table>	x	$f(x)$	-0.1	5.30000	0.0	2.00000	0.2	3.19000	0.3	1.00000	4	CO1
x	$f(x)$												
-0.1	5.30000												
0.0	2.00000												
0.2	3.19000												
0.3	1.00000												
Q2	Using finite differencing, write the expressions for following derivatives: a) $\frac{\partial^2 f}{\partial x^2}$ b) $\frac{\partial^2 f}{\partial x \partial y}$	4	CO1										
Q3	What is a positive definite matrix? Check if the given matrix is positive definite or not? $A = \begin{bmatrix} 4 & 3 & 0 \\ 3 & 4 & -1 \\ 0 & -1 & 4 \end{bmatrix}$	4	CO1										
Q4	What are Newton Coates formula? Discuss their limitations.	4	CO1										
Q5	Find the eigen values of the following matrix: $\begin{bmatrix} 3 & 2 & -1 \\ 1 & -2 & 3 \\ 2 & 0 & 4 \end{bmatrix}$	4	CO1										
SECTION B (4Qx10M= 40 Marks)													
Q6	A car traveling along a straight road is clocked at a number of points. The data from the observations are given in the following table, where the time is in seconds, the distance is in feet, and the speed is in feet per second.	10	CO3										

	<table border="1"> <tbody> <tr> <td>Time</td> <td>0</td> <td>3</td> <td>5</td> <td>8</td> <td>13</td> </tr> <tr> <td>Distance</td> <td>0</td> <td>225</td> <td>383</td> <td>623</td> <td>993</td> </tr> <tr> <td>Speed</td> <td>75</td> <td>77</td> <td>80</td> <td>74</td> <td>72</td> </tr> </tbody> </table> <p>Use a Hermite polynomial to predict the position of the car and its speed when $t = 10$ s.</p> <p style="text-align: center;">OR</p> <p>Construct a natural cubic spline to approximate $f(x) = e^{-x}$ by using the values given by $f(x)$ at $x = 0, 0.25, 0.75,$ and 1.0. Integrate the spline over $[0,1]$, and compare the result to $\int_0^1 e^{-x} dx = 1 - \frac{1}{e}$.</p>	Time	0	3	5	8	13	Distance	0	225	383	623	993	Speed	75	77	80	74	72		
Time	0	3	5	8	13																
Distance	0	225	383	623	993																
Speed	75	77	80	74	72																
Q7	<p>A particle of mass m moving through a fluid is subjected to a viscous resistance R, which is a function of the velocity v. The relationship between the resistance R, velocity v, and time t is given by the equation</p> $t = \int_{v(t_0)}^{v(t)} \frac{m}{R(u)} du$ <p>Suppose that $R(u) = -v\sqrt{v}$ for a particular fluid, where R is in newtons and v is in m/s. If $m = 10$ kg and $v(t_0) = 10$ m/s, approximate the time required for the particle to slow to $v = 5$ m/s.</p>	10	CO4																		
Q8	<p>Use RK2 method to numerically solve the following ODE:</p> $\frac{dy}{dt} = \frac{2 - 2ty}{t^2 + 1}, \quad 0 \leq t \leq 1, \quad y(0) = 1, \quad \text{with } h = 0.1$ <p>If the actual solution is given as</p> $y = \frac{2t + 1}{t^2 + 1}$ <p>Prepare a table of the error between the approximated and actual values at different times.</p>	10	CO4																		
Q9	<p>A projectile of mass $m = 0.11$ kg shot vertically upward with initial velocity $v(0) = 8$ m/s is slowed due to the force of gravity, $F_g = -mg$, and due to air resistance, $F_r = -kv v$, where $g = 9.8$ m/s² and $k = 0.002$ kg/m. The differential equation for the velocity v is given by</p> $m \frac{dv}{dt} = -mg - kv v $ <p>(a) Find the velocity after 0.1, 0.2, ..., 1.0 s (b) To the nearest tenth of a second, determine when the projectile reaches its maximum height and begins falling.</p>	10	CO4																		
SECTION-C																					
(2Qx20M=40 Marks)																					
Q10	<p>(a) Using 3-step Adam's Bashforth method, solve the following time-dependent ODE:</p> $\frac{dy}{dt} = \frac{y}{t} - \left(\frac{y}{t}\right)^2, \quad 1 \leq t \leq 2, \quad y(1) = 1$ <p>Take $h = 0.2$. The actual solution is $y(t) = \frac{t}{1 + \ln t}$ (10 Marks)</p>	20	CO4																		

	<p>(b) Discretize the Poisson Equation given below using finite difference method:</p> $\frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} = -3 \quad 1 < x < 2, \quad 1 < y < 2$ $u(x, 1) = 2x^2, \quad u(x, 2) = 3(x - 2)^2, \quad 1 \leq x \leq 2$ $u(1, y) = 3y^2, \quad u(2, y) = 2(y - 1)^2, \quad 1 \leq y \leq 2$ <p>Use $h = k = \frac{1}{2}$.</p> <p>Write the discretized equations in terms of $A\mathbf{u} = \mathbf{b}$, where A is the coefficient matrix, \mathbf{u} is the unknown and \mathbf{b} is known vector. Discuss the solution strategy. (10 Marks)</p> <p style="text-align: center;">OR</p> <p>(a) Using 3-step Adam's Moulton method to solve the following ODE:</p> $\frac{dy}{dt} = -5y + 5t^2 + 2t, \quad 0 \leq t \leq 1, \quad y(0) = 1/3$ <p>Take $h = 0.1$. The actual solution is $y(t) = t^2 + \frac{1}{3}e^{-5t}$ (10 Marks)</p> <p>(b) Discretize the Laplace equation given below using Finite difference method:</p> $\frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} = 0 \quad 1 < x < 2, \quad 0 < y < 1$ $u(x, 0) = 2 \ln x, \quad u(x, 1) = \ln(x^2 + 1), \quad 1 \leq x \leq 2$ $u(1, y) = \ln(y^2 + 1), \quad u(2, y) = \ln(y^2 + 4), \quad 0 \leq y \leq 1$ <p>Use $h = k = \frac{1}{3}$.</p> <p>Write the discretized equations in terms of $A\mathbf{u} = \mathbf{b}$, where A is the coefficient matrix, \mathbf{u} is the unknown and \mathbf{b} is known vector. Discuss the solution strategy. (10 Marks)</p>		
Q11	<p>Stress-strain relationships and material properties of a cylinder alternatively subjected to heating and cooling may be studied using the following equation</p> $\frac{\partial^2 T}{\partial r^2} + \frac{1}{r} \frac{\partial T}{\partial r} = \frac{1}{4K} \frac{\partial T}{\partial t}, \quad \frac{1}{2} < r < 1, \quad 0 < T$ <p>where $T = T(r, t)$ is the temperature, r is the radial distance from the center of the cylinder, t is time, and K is a diffusivity coefficient.</p> <p>Find the approximations to $T(r, 10)$ for a cylinder with outside radius 1, given the initial and boundary conditions:</p> $T(1, t) = 100 + 40t, \quad T\left(\frac{1}{2}, t\right) = t, \quad 0 \leq t \leq 10$	20 Marks	CO4

$$T(r, 0) = 200(r - 0.5), \quad 0.5 \leq r \leq 1$$

Use BTCS (backward in time and centered in space) with $K = 0.1$, $k = 0.5$ and $h = \Delta r = 0.1$.